

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 April 2005 (14.04.2005)

PCT

(10) International Publication Number
WO 2005/032731 A1

(51) International Patent Classification⁷: **B06B 1/16**

(21) International Application Number:
PCT/GB2004/004157

(22) International Filing Date:
30 September 2004 (30.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0323174.3 3 October 2003 (03.10.2003) GB

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and
(72) Inventor: O'CONNOR, Joe [GB/GB]; 18 Cregglea, Clandy, Co. Londonderry BT47 4HU (GB).

(74) Agent: MURGITROYD & COMPANY; Scotland House, 165-169 Scotland Street, Glasgow G5 8PL (GB).


Published:

— with international search report

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VARIABLE VIBRATOR MECHANISM



(57) Abstract: A variable vibrator mechanism (10) for feeder machines. The vibrator mechanism (10) includes a first member (12) and a second member (14) arranged telescopically with one another. The first member (12) and second member (14) have eccentric weights (axially offset) (16, 26), and are adapted such that the rotational displacement between the eccentric weights (16, 26) is varied by varying the longitudinal displacement between the first and second member (12, 14). Thus allowing the vibrational characteristics of the vibrator to be adjusted by simply varying the displacement between the first and second members (12, 14).

WO 2005/032731 A1